

TECHNICAL DATA SHEET

KEIM BETONSCHNELLREINIGER

1. PRODUCT DESCRIPTION

Hexafluorosilicic acid based cleaning agent for concrete surfaces, which, when applied, reacts to form compounds harmless to the building.

2. FIELD OF APPLICATION

Removal of release agent residues on new concrete surfaces. KEIM Betonschnellreiniger may also be used as a cleaning agent for existing concrete or render surfaces contaminated with oily/greasy substances.

3. PRODUCT PROPERTIES

When correctly used, KEIM Betonschnellreiniger is completely neutralised.

- Aqueous
- Practically no solvents added (max. 2%)

Material characteristics:

pH-value: ≈ 1 (acidic)
Density: 1.1 - 1.2 g/cm³

Colour shades:

Transparent, colourless

4. APPLICATION INSTRUCTIONS

Dilution:

Depending on the quantity of release agent residues and soiling present, dilute KEIM Betonschnellreiniger with water in a ratio of 1:3 to 1:5.

When cleaning concrete surfaces which are subsequently to receive only a transparent finish, the product must be diluted with water to a ratio of at least 1:5.

At lower levels of dilution, permanent, light-coloured residues may form on the concrete which will not be concealed by transparent finishes. (It is recommended to coat test areas in this case). These permanent residues are completely harmless and can be straightforwardly overcoated with any paints from the KEIM Concretal®-system.

Application:

Prewet concrete surfaces before applying KEIM Betonschnellreiniger, applying sufficient water to create a moist, matt surface. Then brush on a thin coat of diluted KEIM Betonschnellreiniger as required. The reaction proceeds immediately. Treated surfaces should then be washed by hosing down with plenty of water. Treated interior surfaces may also be washed down with wet cloths.

Due to its dirt content any washing water from cleaning should be disposed of in accordance with applicable regulations.

Application conditions:

Ambient and substrate temperature > +5 °C.

Waiting times:

Surface protection treatments from the KEIM Concretal®-system may only be applied once the substrate is completely dry, at the earliest after 12 hours.

Consumption:

Single application onto a smooth substrate: approx. 0.05 J/m^2 .

Cleaning of tools:

Clean with water immediately after use.

5. PACKAGING

5 | or 20 | containers

6. STORAGE

Shelf life is approx. 12 months in a sealed container under cool, but frost-free conditions. Protect from heat and direct sunlight.

7. DISPOSAL

EC Waste Code No. 06 01 06

Any residues must be emptied out of containers before recycling.

8. SAFETY INSTRUCTIONS

Gisbau Product-Code/ Giscode: GF50

Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water. Protect the eyes and skin from splashes. Keep out of reach of children.

Please refer to EC Safety Data Sheet.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.