



KEIM STS 2

1. Product Information

Keim STS 2 is a dichloromethane based paint stripper having low odour characteristics.

2. Field Of Application

For removal of existing paint finishes from substrates prior to the application of Keim Mineral Paint systems.

3. Product Characteristics

- Low odour
- 20 minutes to 2 hours operation

Material Data:

Relative density: 1.1 g/cm³
Flash point: >95°C
Solubility: Easily soluble in water
Colour: White

4. Application

Substrate Preparation:

Keim STS 2 should be liberally applied by brush and allowed to remain undisturbed for some 20-40 minutes when bubbling of the paint film will indicate good separation. Materials can then be removed using broad bladed scrapers while the paint stripper is still wet and all areas washed down with copious quantities of warm water to remove all traces of paint stripper.

Please note that operatives should wear rubber hand protection and eye protection during operations and all surrounding materials should be well protected. Operatives should also wear brown solvent/Organic Vapour/AX filter masks during operations.

Air and surface temperature >5°C

Consumption:

0.5 – 0.7 kg per square metre depending on the number of paint layers discovered.

Tools:

Clean immediately after use with water.

5. Packaging

5 & 25 kg containers

6. Storage

Approx. 12 months, if kept cool, but frost free in tightly closed containers.

7. Identification Ref Ordinance Of Dangerous Materials

Not applicable

8. Danger Class In Goodstraffic

Class 6.1
UN 1593
Packing Group III

9. Safety Instructions

Operatives should wear rubber hand protection and eye protection during operations and all surrounding materials should be well protected. Operatives should also wear brown solvent/Organic Vapour/AX filter masks during operations.

Cover surfaces which are not to be treated, in particular plants, etc. Keep out of reach of children.

Refer to appropriate COSHH data sheets.
